

Full Function Handy DMMs for Lab and Field Services!

Full $\mu\text{A}/\text{mA}/10\text{A}$ Ranges, Audible + Visible BeepLit™ Continuity, AutoV + Ghost Voltage Buster, VFD V & Hz Fundamentals, Hi & Lo EF-Detection, Records Min/Max/Average, Relative Zero, BeepJack™ Warning!



CE

BM230 Series
Practical Multimeter

BRYMEN®

BRIGHT PEOPLE'S CHOICE



● **BM235**



● **BM233**



● **BM231**

235	233	231	FUNCTIONS & FEATURES
●	●	●	3-5/6 Digits 6,000 Counts Large Easy To Read LCD Display
●	●	●	Fast Measurements, 5/Sec; Fully Auto-Ranging
●	●	●	Intelligent Auto Power Off
●	●	●	True RMS AC Conversion
●	●	●	Data Hold
●	●	●	Records Max/Min Readings & Calculates Avg Readings Over Time
●	●	●	VFD V & Hz Fundamental Readings Of Most Variable-Frequency-Drives
●	●	●	Paper white Back-Lighted LCD Display
●	●	●	BeepLit™ Continuity. Features Audible Beep & Visible Backlight Effects
●	●	●	Relative Zero Mode
●	●	●	Non-Contact EF-Detection (NCV) With Hi/Lo Selectable Sensitivities
●	●	●	Probe-Contact EF-Detection For More Precise Indication Of Live
●			AutoV LoZ Feature. Automatic DC & AC 1000V Selection With Low Initial Impedance To Drain Ghost Voltages
●	●	●	DC/AC V Ranges 600.0mV To 1000V
●	●	●	Ohms Ranges 600.0Ω To 60.00MΩ
●	●		Cx Ranges 20.00nF to 10.00mF For Start & Run Motor Capacitors
●	●		Line Level Frequency Ranges 99.99Hz To 50.00kHz
●	●	●	DC/AC μA, mA & A Ranges 600.0μA To 10.00A (20A for 30s / 5 mins cool down)
●			Type-K Temperature Readings -40°C To 400°C or -40°F To 752°F
●	●	●	Beep-Jack™ Input Warning Against Improper μAmA/A-Terminals Plug In
●	●	●	Diode Tester
●	●	●	Rugged Fire Retarded Housing
●	●	●	Replaceable Protective Holster With Probe-Holders & Tilt-Stand
●	●	●	Optional Purchase Magnetic Hanger
●	●	●	Batteries And Fuses Access Door
●	●	●	Transient Protection Up To 6kV 1.2/50μs Lightning Surge
●	●	●	LVD: EN61010-1/-2-030/-2-033 CAT-II 1kV, CAT-III 600V & CAT-IV 300V
●	●	●	EMC: EN61326-1:2013

Compact Yet Optimized For Your Daily Service!

Full μ A/10A Ranges, BeepLit™ Continuity, Hi/Lo EF-Detection, LoZ AutoV, VFD V/Hz, °C/°F, Min/Max/Avg, BeepJack™ Warning

White Display Backlight
For Easy Viewing In The Dark

Auto & Manual-ranging
Auto-ranging With
Manual-ranging Override

True RMS Measurements
For Non-sinusoidal Waveforms
Of AC Voltages & AC Currents

Large 6000 Counts LCD Display
5/sec Fast Nominal Update Rate

Function Selection
Toggle Conveniently Between
Primary & Secondary Functions

Hz Of Line Level Voltage
Measures Noisy High Voltage
ACV Frequencies

VFD V & Hz Feature
Measures Fundamental
Voltage & Frequency Of Most
Variable-Frequency-Drives

High Impedance Voltage
1000VAC/DC Measuring Capabilities;
High Input Impedance For
Load Sensitive Circuits

AutoV LoZ Feature
Automatic Selection Of
LoZ DCV And LoZ ACV

Ghost-voltage-buster
AutoV Loz Drains Ghost/ Stray Voltages
Leaving Only Hard Signals
On Meter Readings

Beep-jack™ Audible Warning
Beeps Against Improper A-terminal
Plug In. Decreases Risks Of Damage

Protective Holster
With Holders For Probe Storage
And "third Hand" Feature,
Replaceable & Washable

EMC
Meets EN61326-1:2013

LVD Safety
Meets EN61010-1/-2-030/-2-033
CAT II 1kV & CAT III 600V

Max Min Avg Record
Record Max/Min And
Calculates Average
Readings Over Time

Relative Zero Mode
For Convenient Readings
Comparison & Offset

Data Hold
Freezes The Displaying
Reading For Later View

Hi/Lo Senses EF-Detection
Both Non-contact (NCV) &
Single-probe Voltage Detection
For Identifying Live Lines

Full μ A, mA & A Ranges
6 Full Current Ranges With
1000V HBC Fuses Protected

BeepLit™ Continuity
Quick Open-short Tests.
Beep and Backlight Effects
For Noisy Environments

Type-k Temperature
Selectable °C & °F Readings

Intelligent Auto-power-off
To Extend Battery Life

Transient Protection
Up To 6kV 1.2/50 μ s Lightning Surge;
Superb Protection For Serious Users



GENERAL SPECIFICATION

Display: 3-5/6 digits 6,000 counts
Update Rate: 5 per second nominal
Operating Temperature: -10°C to 45°C
Relative Humidity: Maximum relative humidity 80% for temperature up to 31°C decreasing linearly to 50% relative humidity at 45°C
Altitude: Operating below 2000m
Storage Temperature: -20°C ~ 60°C, < 80% R.H. (with battery removed)
Temperature Coefficient: Nominal 0.15 x (specified accuracy)/°C @ (-10°C ~ 18°C or 28°C ~ 45°C), or otherwise specified
Sensing: True RMS sensing
Pollution Degree: 2
Safety: Double insulation per IEC/UL/EN61010-1 Ed. 3.0, IEC/UL/EN61010-2-030 Ed. 1.0, IEC/UL/EN61010-2-033 Ed. 1.0, IEC/UL/EN61010-031 Ed. 1.1 and the corresponding CAN/CSA-C22.2 regulations to Measurement CAT II 1000V, CAT III 600V and CAT IV

300V AC & DC
Transient Protection: 6.0kV (1.2/50µs surge)
Terminals (to COM) Measurement Category: V / mAµA / A: Category II 1000V, CAT III 600V and CAT IV 300V AC & DC.
E.M.C.: Meets EN61326-1:2006
 In an RF field of 3V/m:
 Temperature function is not specified
 Ohm function:
 Total Accuracy = Specified Accuracy + 15 digits
 Other functions:
 Total Accuracy = Specified Accuracy
 Performance above 3V/m is not specified
Overload Protection:
 µA & mA: 0.4A/1000V DC/AC rms, IR 30kA, F fuse
 A: 11A/1000V DC/AC rms, IR 20kA, F fuse
V & AutoV: 1100V DC/AC rms
mV, Ohm & others: 1000V DC/AC rms
Low Battery: Below approx. 2.5V

Power Supply: 1.5V AAA Size battery X 2
Power Consumption (typical): 3.2mA
APO Consumption (typical): 10µA
APO Timing: Idle for 30 minutes
Dimension: 161*80*50mm L*W*H (With Holster)
Weight: Approx. 334 gm (With Holster)
Special Features: AutoV (LoZ) (BM235 only); VFD; Auto-ranging MAX/MIN/AVG Record; Backlighted LCD; Auto-ranging Relative Zero mode; Display Hold; EF-Detection (NCV); BeepJack™ on µAmA/A terminals
Accessories: Test lead pair; Batteries installed; Users manual; BKP60 banana plug type-K thermocouple (BM235 only)
Optional Purchase Accessories: BKB32 banana plug to type-K socket plug adaptor (BM235 only); BMH-01 magnetic hanger; BMP-25x soft carrying pouch

Electrical Specification

Accuracy is given as ±(% of reading digits + number of digits) or otherwise specified @ 23°C ± 5°C
 ACV & ACA accuracies are specified from 1 % to 100 % of range or otherwise specified. Maximum Crest Factor <2:1 at full scale & <4:1 at half scale, and with frequency components fall within the meter specified frequency bandwidth for non-sinusoidal waveforms

AC Voltage

RANGE	Accuracy
50Hz ~ 60Hz	
6.000V, 60.00V, 600.0V, 1000V	0.7% + 3d
45Hz ~ 440Hz	
6.000V, 60.00V, 600.0V, 1000V	2.0% + 3d
10Hz ~ 500Hz	
60.00mV, 600.0mV	1.0% + 3d
500Hz ~ 800Hz	
60.00mV, 600.0mV	2.0% + 3d

Input Impedance: 10MΩ, 54pF nominal

VFD_ACV (with Low Pass Filter)

RANGE	Accuracy ¹⁾
10Hz ~ 440Hz (fundamental)	
600.0V, 1000V	2.0% + 3d

¹⁾Not specified for fundamental frequency > 440Hz

AutoV_ACV (BM235 only)

RANGE	Accuracy ¹⁾
45Hz ~ 440Hz	
600.0V, 1000V	2.0% + 3d

¹⁾Not specified at <1VAC

Threshold: > 1VAC nominal

Input Impedance:

Initially approx. 2.1kΩ, 164pF nominal; Impedance increases abruptly within a fraction of a second as display voltage is above 50V (typical). Ended up impedances vs display voltages typically are:

12kΩ @100V
 100kΩ @300V
 240kΩ @600V
 580kΩ @1000V

DC Voltage

RANGE	Accuracy
60.00mV, 600.0mV, 6.000V, 60.00V, 600.0V, 1000V	0.3% + 2d

Input Impedance: 10MΩ, 54pF nominal

AutoV_DCV (BM235 only)

RANGE	Accuracy ¹⁾
600.0V, 1000V	2.0% + 3d

¹⁾Not specified at <1VDC

Threshold: > +1.0VDC or < -1.0VDC nominal

Input Impedance:

Initially approx. 2.1kΩ, 164pF nominal; Impedance increases abruptly within a fraction of a second as display voltage is above 50V (typical). Ended up impedances vs display voltages typically are:

12kΩ @100V
 100kΩ @300V

240kΩ @600V
 580kΩ @1000V

Ohm

RANGE ¹⁾	Accuracy
600.0Ω, 6.000KΩ	0.3% + 3d
60.00KΩ, 600.0KΩ	0.5% + 3d
6.000MΩ ²⁾ , 60.00MΩ ³⁾	0.9% + 2d ⁴⁾

¹⁾Open Circuit Voltage: 1.6VDC typical

²⁾Constant Test Current: 0.2µA Typical

³⁾Constant Test Current: 0.02µA Typical

⁴⁾5%+20d @ >30MΩ

BeepLit™ Continuity Tester

Continuity Threshold: Between 30Ω and 480Ω

Response time: 64ms

Latch time: 128ms

Audible Response: Beep sound

Visible Response: LCD Backlight

Capacitance (BM233 & BM235 only)

RANGE	Accuracy
20.00nF, 200.0nF	1.5% + 8d
2000nF, 20.00µF, 200.0µF, 2000µF	1.5% + 2d
10.00mF	4.5% + 10d

Accuracies with film capacitor or better

Diode Tester

RANGE	Accuracy
3.000V	0.9% + 2d

Test Current: 0.3mA typical

Open Circuit Voltage: < 3.2VDC typical

DC Current

RANGE	Accuracy	Burden Voltage
600.0µA, 6000µA	1.0% + 3d	0.1mV/µA
60.00mA, 600.0mA	0.7% + 3d	1.9mV/mA
6.000A, 10.00A ¹⁾		0.04V/A

¹⁾10A continuous, >10A to 20A for 30 seconds max with 5 minutes cool down interval

AC Current

RANGE	Accuracy	Burden Voltage
50Hz ~ 400Hz		
600.0µA, 6000µA	1.5% + 3d	0.1mV/µA
60.00mA, 600.0mA	1.0% + 3d	1.9mV/mA
6.000A, 10.00A ¹⁾		0.04V/A

¹⁾10A continuous, >10A to 20A for 30 seconds max with 5 minutes cool down interval

Temperature (BM235 only)

RANGE	Accuracy
-40.0 °C ~ 99.9 °C	1% + 1 °C
100 °C ~ 400 °C	
-40.0 °F ~ 99.9 °F	1% + 2 °F
100 °F ~ 752 °F	

Type-K thermocouple range & accuracy not included

Line Frequency (BM233 & BM235 only)

Function	Sensitivity (Sine RMS)	Range
60mV, 600mV	50mV	10Hz - 50kHz
6V	3V	10Hz - 50kHz
60V	5V	10Hz - 50kHz
600V	50V	10Hz - 1kHz
1000V	500V	10Hz - 1kHz
VFD 600V	50V	10Hz - 1kHz
VFD 1000V	500V	10Hz - 1kHz
600µA, 6000µA	500µA	10Hz - 5kHz
60mA, 600mA	50mA	10Hz - 5kHz
6A, 10A	8A	50Hz - 1kHz

Accuracy: 0.03% + 2d

Non-Contact EF-Detection

Bar-Graph Indication	EF-H (Hi Sensitivity)	EF-L (Lo Sensitivity)
	Typical Voltage (Tolerance)	
-	10V (3V~19V)	40V (16V~71V)
--	20V (10V~38V)	80V (32V~142V)
---	40V (21V~79V)	160V (63V~285V)
----	80V (40V~156V)	300V (105V~608V)
-----	160V (>80V)	500V (>300V)

Indication: Bar-graph segments & audible beep tones proportional to the field strength

Detection Frequency: 50/60Hz

Detection Antenna: Top-left end of the meter

Probe-Contact EF-Detection: For more precise indication of live wires, such as distinguishing between live and ground connections, use direct contact testing with one single test-probe via the input terminal COM or V. The COM terminal (Black) has the best sensitivity.

